



SHRINK TECH SYSTEMS

www.shrinktechsystems.com

MODEL TP-14



Manufactured
In The U.S.A.




ADJUSTABLE CROSSSEAL
OPENING FROM THE
OPERATOR CONTROL
PANEL 1" TO 14"



THE OPERATOR COMMAND CENTER
IS CONVENIENTLY LOCATED AND
FEATURES A TWO LINE L.E.D.
DISPLAY WITH 5 BUTTON DIRECT
ACCESS MACHINE CONTROL FOR
SIMPLE SETUP. COMMAND CENTER
ALSO HAS 3 OPERATIONAL MODE
LIGHTS AND CAPABILITY OF
STORING 4 PRODUCT PRESETS.

ADJUSTABLE SYSTEMS SPEED
FROM 20 TO 100 F.P.M.
CONVEYORS
SOFT STOP/START
SELECTABLE
FROM OPERATOR
CONTROL PANEL



PATENTED "UNIVERSAL"
SIDE SEAL WITH "PNEU-TRAC"
FILM GUIDING SYSTEM AND
INDEPENDENT HEIGHT
ADJUSTMENT

INTEGRATED SCRAP WIND-UP
WITH SELF COMPENSATING
WINDING SPEED CONTROL TO
AUTOMATICALLY
MATCH MACHINE SPEED



EASY LOAD, FLOOR HEIGHT
FILM CRADLE WITH HEAVY DUTY
FILM SEPARATOR AND 15 ROWS
OFFILM PERFORATION WHEELS
MAXIMUM C.F. FILM WIDTH 35"



PRODUCT CAPACITY WITH HEIGHT RANGE
UP TO 14" WIDTH OF PRODUCT TO 21"
AND INFINITE LENGTH ALL HAND CRANK
ADJUSTMENTS HAVE CORRESPONDING
SCALES FOR EASE OF PRODUCT CHANGE OVER

PNEUMATIC: 80 PSI
ELECTRICAL: 120VAC, 15 AMP
VARIABLE SPEED: 20 to 100 F.P.M.
CONVEYOR HEIGHT: ADJUSTABLE 34" TO 37"
MACHINE SIZE: 144" LENGTH 53" WIDTH 60" HEIGHT

1226 AMBASSADOR BLVD.
SAINT LOUIS, MISSOURI 63132
PHONE: 314.997.4259 FAX: 314.995.7006